

# VP-710 法蘭式隔膜閥

## Diaphragm Valve (Flanged)

- Pressure rating: 1/2"~3" 150 PSI, 4"~6" 72 PSI, 8" 43 PSI @73.4°F(23°C)

(Working pressure is varified by diaphragm material and working temperature.)

- Smooth operation with clear indication of opening / closing through the gauge cover
- Low maintenance cost with replaceable diaphragm and long service life
- Adjustable stopper can avoid over tightness.
- Alternative material for stem and sleeve: SUS 304 / 316
- 工作壓力：1/2"~3" 150 PSI, 4"~6" 72 PSI, 8" 43PSI @73.4°F(23°C)  
(因DIAPHRAGM之材質、工作溫度不同而壓力會不同)
- 關閉程度可清楚於透明罩上顯示
- 膜片可替換，保養管理容易
- 可調整的阻擋螺帽設計，可以防止關閉時手輪之壓力過當
- 法蘭片底部有平面設計，便於安裝及放置
- 中心柱及套筒可選用 SUS 304 / 316 材質

Type 品號	Size 尺寸	Standard 規格	Material 材質	Gasket 墊片	O-ring O環	Diaphragm 隔膜片	End type 接口	Bolt 螺栓
VP-710	1/2"~8"	ANSI, JIS, DIN	PVC	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316
VP-711	1/2"~8"	ANSI, JIS, DIN	CPVC	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316
VP-713	1/2"~8"	ANSI, JIS, DIN	PVDF	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316
VP-714	1/2"~8"	ANSI, JIS, DIN	PP	PTFE	NBR	EPDM, FPM, PTFE	Flanged	SUS 304 / 316



### Caution!

- (1) After installed, should inspect the set nut and stopper (above the stem) frequently, to make sure the nuts are tight.
- (2) The valve is completely closed when handwheel can't turn more with normal torque, but it will cause the unrecoverable divulsion of diaphragm if the handwheel is continuously forced to turn in such above condition!

### 注意!

- (1) 安裝使用中，應常檢視中心柱上端開度指示螺帽組需保持無鬆動狀態
- (2) 手輪正常旋緊至無法繼續時即代表閥門已完全關閉，切勿再強迫旋轉避免造成無法修復之膜片撕裂現象！

Nom.	SIZE	15mm	20mm	25mm	40mm	50mm	65mm	80mm	100mm	125mm	150mm	200mm
		(1/2")	(3/4")	(1")	(1-1/2")	(2")	(2-1/2")	(3")	(4")	(5")	(6")	(8")
JIS	D	95	100	125	140	155	175	185	210	250	291	343
	D1	70	75	90	105	120	140	150	175	210	240	290
	n-ae	4-ø15	4-ø15	4-ø19	4-ø19	4-ø19	4-ø19	8-ø19	8-ø19	8-ø23	8-ø23	12-ø23
	L	110	120	130	180	210	250	280	340	410	480	570
ANSI	D	89	98	108	127	152	178	191	229	250	291	343
	D1	61	70	79	98	121	140	152	191	216	241	299
	n-ae	4-ø16	4-ø16	4-ø16	4-ø16	4-ø19	4-ø19	4-ø19	8-ø19	8-ø23	8-ø23	8-ø23
	L	108	150	150	176	202	250	264	329	410	480	570
DIN	D	95	105	115	150	165	185	200	220	250	291	343
	D1	65	75	85	110	125	145	160	180	210	240	295
	n-ae	4-ø14	4-ø14	4-ø14	4-ø18	4-ø18	4-ø18	8-ø18	8-ø18	8-ø18	8-ø22	8-ø22
	L	130	150	160	200	230	290	310	350	410	480	570
JIS	UPVC,CPVC	12	13	13	17	20	22	22	23	24	26	30
	PP,PVDF	13	14	14	18	21	23	24	25	25	25	35
ANSI	UPVC,CPVC	12	15	18	15	19	20	20	23	24	26	30
	PP,PVDF	13	16	19	16	20	21	23	25	25	28	35
DIN	UPVC,CPVC	19	20	20	19	22	22	24	24	24	26	30
	PP,PVDF	20	21	21	20	23	23	26	26	25	28	35
D2	54x70	63x78	63x88	125	148	182	203	255	330	392	432	
D3	95	95	110	150	150	210	210	250	405	405	405	
d	13	18	25	41	52	67	78	100	125	148	198	
H1	85	94	98	130	148	189	250	275	334	334	450	
H2	130	137	160	200	225	268	343	383	476	476	627	
l	10	12	15	22	31	39	48	60	70	70	95	

NO	PART	MATERIAL	Q'TY
1	BODY 本體	UPVC,CPVC,PVDF,PP	1
2	BONNET 上蓋	UPVC,CPVC,PVDF,PP,PP+GF	1
3	COMPRESSOR 壓縮筒	PP+GF,PVDF	1
4	HANDWHEEL 把手輪	PP	1
5	SLEEVE 中心套筒	C3602,SUS	1
6	STEM 中心柱	C3602,SUS	1
7	DIAPHRAGM 隔膜片	EPDM,FPM,PTFE	1
8	CAP 頂蓋螺帽	UPVC,CPVC,PVDF,PP,PP+GF	1
9	COMPRESSOR PIN 彈簧銷	SUS304	1
10	INSERTED METAL 膜片螺絲	C3602,SUS	1
11	GREASE NIPPLE 黃油嘴	C3602 2-1/2"~8"	1
12	BOLT&WASHER 螺絲組	SUS304,SUS316	1/2"~3/4"---4 SET 1"~2"---6 SET
13	INSERTED NUT 本體埋螺	C3602,SUS304 SUS316	2-1/2"~4"---8 SET 6"---12 SET
14	NUT&WASHER 螺帽組	SUS304,SUS316	8"---16 SET
15	THRUST RING & BEARING 薄片&止推軸承	PTFE 1-1/2"~3",SUS 4"~8"	1
16	STOPPER 阻擋螺帽	SUS304	1
17	SET NUT 固定螺帽	SUS304	1
18	GAUGE COVER 透明罩	AS	1
19	SHEET GASKET 墊片	EPDM	1
20	SHEET RING 中心平華司	SUS304	1
21	INDICATIVE WASHER 指示華司	ABS	1
22	O-RING 上蓋O環	NBR	1
23	NAME PLATE 銘牌	UPVC	1~6
24	PRESSURE PLATE 壓板	SUS304	1~6
25	CASING 套管	UPVC,CPVC,PVDF,PP 8" only	1

